

DC BATTERY BACKUP BELT DRIVE WI-FI[®] GARAGE DOOR OPENER FEATURE RICH, OFFERING ULTIMATE GARAGE PROTECTION.



- SECURE**
- AUTOMATIC GARAGE DOOR LOCK CAPABLE:** DEADBOLT LOCKS THE GARAGE DOOR, MAKING IT VIRTUALLY IMPENETRABLE (2 MAX., SOLD SEPARATELY).
 - TIMER-TO-CLOSE** CAN BE PROGRAMMED TO CLOSE THE DOOR AFTER A SET AMOUNT OF TIME.
 - SECURITY+ 2.0[®]** SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.
 - POSILOCK[®]** ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.
 - ALERT-2-CLOSE** SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ[®].
 - MOTION DETECTOR** LIGHTS THE WAY AUTOMATICALLY.
 - THE PROTECTOR SYSTEM[®]** INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.
- QUIET & RELIABLE**
- BELT DRIVE SYSTEM** FOR POWERFUL, ULTRA-QUIET PERFORMANCE.
 - SOFT START/STOP** FOR SMOOTH OPERATION.
 - DC MOTOR** IS PURPOSEFULLY DESIGNED FOR QUIET, LONG-LASTING SERVICE.
 - BATTERY BACKUP** ENSURES GARAGE ACCESS EVEN WHEN THE POWER IS OUT.
 - WARRANTY** LIFETIME MOTOR AND BELT, 5-YEAR PARTS, 1-YEAR BATTERY AND ACCESSORIES.
- SMART**
- BUILT-IN WI-FI** FOR THE EASIEST WAY TO CONNECT THE GARAGE.
 - FREE MyQ MOBILE APP** SO USERS KNOW THEIR HOME IS SECURE.
 - REAL-TIME ALERTS** INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.
 - MONITOR AND CONTROL** THE OPENER FROM ANYWHERE USING MOBILE DEVICES.

INCLUDED ACCESSORIES:

- Smart Control Panel[®]** LCD display enables simple programming and adjustment of settings. **880RGDW**
- 3-Button Remote Control** Operates up to 3 openers or MyQ Light Accessories. **893RCX**
- Integrated Battery Backup** Powers up the opener when the power is out. **485LM**

POWERFUL ADD-ONS:

- Automatic Garage Door Lock Capable** Deadbolts the garage door automatically every time it closes. **841LG**
- Remote Light Control** Plug in any lamp to this device to control it with a smartphone or garage remote. **825LM**
- Mini Universal Remote Control** Compact and portable to provide quick, easy garage access. **374UT**
- MyQ Remote LED Light** Provides convenient, secure access from outside the garage with a 4-digit PIN. **827LG**

MASTERFUL ENGINEERING.

MOTOR

- 12V DC
- 53 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER

- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL Listed
- 6' Power Cord (3-Prong)

MECHANICS

- **Steel Chassis, T-Rail and Trolley**
- **Full Reinforced Belt Drive Mechanism** (63:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **DC WiFi® Logic Board** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050DCTWFLK)
- **2 Lock Terminals** Allow up to 2 Locks to Be Connected (Sold Separately)



DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	125"	140"	164"
Max. Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

STANDARD SPECS.

SECURITY

SECURITY+ 2.0®

RADIO CONTROLS

- Operating Temperature: -40°F to 150°F
- 3-Button Remote Control
 - Remote Control: 310, 315 and 390 MHz Tri-Band*
 - Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
 - Anti-Burglary Coding

*Tri-band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.


ENCRYPTED CONTROLS

- Smart Control Panel®
 - Timer-to-Close
 - Program Remote controls, Keypads and MyQ Accessories
 - Maintenance Alert System
 - Easy WiFi® Setup



SMART

MyQ® RADIO



50-Channel FHSS (Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER*)

*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING



- Max. 2 100-Watt Lightbulbs
- Adjustable Time
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts
- Disabled in Battery Backup Mode

9" Per second for door to move upward

SPEED

6.5" Per second for door to move downward

SHIPPING.

SHIPPING WEIGHT (in lbs.)

CARTONS (4)

- CARTON 1: 20" x 12" x 10"
 - Garage Door Opener Head
 - Smart Control Panel
 - 3-Button Remote Control
 - The Protector System® Safety Reversing Sensors

- CARTON 2: 10'4" x 5" x 5" (for 7' Rail)
 - Assembled Solid-Steel Belt T-Rail



CARTON 3: 5.31" x 4.63" x 5.13"

- Battery

CARTON 4 (OPTIONAL): 8" x 4.5" x 4"

- Automatic Garage Door Lock

SAFETY AND SECURITY.

- Automatic Garage Door Lock Capable (2 Max.)
- Alert-2-Close/Unattended Close Operation†
- Motion Detection Feature on Control panel
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 40 Remote Controls, 4 Wireless Keyless Entry Systems and 16 MyQ Devices

HomeLink® and the HomeLink House® logo are registered trademarks of Gentex Corporation

†: to reduce the risk of injury to persons, only use alert-2-Close/Unattended Close Operation features when installed with a sectional door.